


Description

The DFS17SU12Z7C1 is a Single Unit SiC MOSFET Power Module. It integrates high performance SiC MOSFET chips designed for the applications such as Motor drives and EV charging.

Features

- 1200V/17mΩ @ $T_j = 25^{\circ}\text{C}$, $V_{GS} = 18\text{V}$
- 175°C maximum junction temperature
- Low Device Capacitances(C_{oss} , C_{rss})
- Faster and More Efficient Switching



Applications

- UPS
- Motor Drive
- EV Charging
- High Voltage DC-DC Converters
- Induction Heating and Welding
- Smart Grid Transmission and Distribution

Circuit diagram




Figure 1. Out drawing & circuit diagram for DFS17SU12Z7C1

Pin Configuration and Marking Information




Figure 2. Pin configuration

Module

Parameter	Conditions	Value	Unit
Isolation Voltage	RMS, f=50Hz, t=1min	3.4	KV
CTI	-	>400	-
Mounting torque for module mounting	M4	1.5	Nm
Weight	-	28	g

Maximum Ratings (T_j =25°C unless otherwise specified)

Symbol	Parameter	Conditions		Ratings	Unit
V _{DSS}	Drain-Source Voltage	G-S Short		1200	V
V _{GSS}	Gate-Source Voltage	D-S Short, AC frequency ≥1Hz, Note1		-10 to +22	V
I _{DS}	DC Continuous Drain Current	V _{GS} =+15V	T _c =25°C	105	A
I _{DS}	DC Continuous Drain Current		T _c =100°C	75	A
I _{DS}	DC Continuous Drain Current	V _{GS} =+18V	T _c =25°C	110	A

I_{DS}	DC Continuous Drain Current	$T_c=100^{\circ}\text{C}$	80	A
I_{DSM}	Pulse Drain Current	Pulse width $\leq 3\mu\text{s}$, $V_{GS} = +15\text{V}$, Note2	313	A
P_{tot}	Total Power Dissipation	$T_c=25^{\circ}\text{C}$	350	W
T_{jmax}	Max Junction Temperature	-	175	$^{\circ}\text{C}$
T_{stg}	Storage Temperature	-	-50 to 175	$^{\circ}\text{C}$

Note1: Recommended Operating Value, +18V/-5V, +15V/-4V

Note2: Pulse width limited by maximum junction temperature

Preliminary datasheet _Ver.A EN

www.leapers-power.com

MOSFET Electrical characteristics (T_j=25°C unless otherwise specified, chip)

Symbol	Item	Condition		Value			Unit
				Min.	Typ.	Max	
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =100uA		1200	-	-	V
I _{DSS}	Zero gate voltage drain Current	V _{DS} =1200V, V _{GS} =0V		-	1	-	μA
V _{GS(th)}	Gate-source threshold Voltage	I _D =35mA, V _{DS} =V _{GS}	T _j =25°C	1.8	2.7	-	V
			T _j =175°C	-	2.05	-	
I _{GSS}	Gate-Source Leakage Current	V _{GS} =22V, V _{DS} =0V	T _j =25°C	-	-	100	nA
R _{DS(on)} (Chip)	Static drain-source On-state resistance	I _D =60A V _{GS} =+15V	T _j =25°C	-	20	-	mΩ
			T _j =175°C	-	29	-	mΩ
		I _D =60A V _{GS} =+18V	T _j =25°C	-	17	22.5	mΩ
			T _j =175°C	-	25	-	mΩ
V _{DS(on)} (Chip)	Static drain-source On-state Voltage	I _D =60A V _{GS} =+15V	T _j =25°C	-	1.20	-	V
			T _j =175°C	-	1.74	-	V
		I _D =60A V _{GS} =+18V	T _j =25°C	-	1.02	1.35	V
			T _j =175°C	-	1.50	-	V
C _{iss}	Input Capacitance	V _D =800V, V _{GS} =0V, f =1MHz, V _{AC} =25mV		-	5814	-	pF
C _{oss}	Output Capacitance			-	177	-	pF
C _{rss}	Reverse transfer Capacitance			-	14.2	-	pF
Q _g	Total gate charge	V _{DD} =800V, I _D =60A, V _{GS} =+15/-5V		-	180	-	nC
R _{Gint}	Internal Gate Resistance	T _j =25°C		-	1.3	-	Ω
t _{d(on)}	Turn-on delay time	V _{DD} =800V I _D =60A V _{GS} =+15/-4V R _{gon} =R _{gofi} =1.0Ω	T _j =25°C	-	45	-	ns
			T _j =150°C	-	39	-	
t _r	Rise time		T _j =25°C	-	18	-	ns
			T _j =150°C	-	16	-	
t _{d(off)}	Turn-off delay time		T _j =25°C	-	20	-	ns
			T _j =150°C	-	25	-	
t _f	Fall time			T _j =25°C	-	11	-

		Inductive load switching operation	T _j =150°C	-	35	-	
E _{on}	Turn-on power dissipation		T _j =25°C	-	492	-	μJ
			T _j =150°C	-	662	-	
E _{off}	Turn-offpower dissipation		T _j =25°C	-	205	-	μJ
			T _j =150°C	-	200	-	
R _{th(j-c)}	FET Thermal Resistance	Junction to Case		-	0.36	0.48	K/W

Body Diode Electrical characteristics (T_j=25°C unless otherwise specified, chip)

Symbol	Item	Condition		Value			Unit
				Min.	Typ.	Max	
V _{SD}	Body Diode Forward Voltage	V _{GS} = -5V	T _j = 25°C	-	4.6	-	V
		I _{SD} = 30A	T _j = 175°C	-	4.2	-	
T _{rr}	Reverse recovery time	V _{DD} = 800V, I _D = 60A V _{GS} = +15/-4V	T _j = 25°C	-	35	-	ns
			T _j = 150°C	-	47	-	
Q _{rr}	Reverse recovery charge	R _{gon} = R _{goff} = 1.0Ω Inductive load switching operation	T _j = 25°C	-	240	-	nC
			T _j = 150°C	-	475	-	
I _{rrm}	Reverse recovery current		T _j = 25°C	-	14	-	A
			T _j = 150°C	-	21	-	A

Test Conditions




Figure 3. Switching time measure circuit




Figure 4. Switching time definition




Figure 5. I_{DS} vs V_{DS}
 $T_J = 25^\circ\text{C}$




Figure 6. I_{DS} vs V_{DS}
 $T_J = 175^\circ\text{C}$




Figure 7. I_{DS} vs V_{DS}
 $V_{GS} = +15\text{V}$




Figure 8. I_{DS} vs V_{GS}
 $V_{DS} = +10\text{V}$




Figure 9. I_{SD} vs V_{SD} (V_F)
 $T_j = 25^\circ\text{C}$




Figure 10. I_{SD} vs V_{SD} (V_F)
 $T_j = 175^\circ\text{C}$




Figure 11. $R_{DS(ON)}$ vs T_j
 $I_D = 60\text{A}$




Figure 12. $R_{DS(ON)}$ vs I_{DS}
 $V_{GS} = +15\text{V}$




Figure 13. V_{GS} vs Q_g

$V_{DS}=800V$, $I_D=60A$, $T_j=25^\circ C$




Figure 14. $V_{GS(TH)}$ vs T_j

$V_{GS}=V_{DS}$, $I_D=35mA$




Figure 15. E_{on} , E_{off} vs R_g

$T_j=25^\circ C$, $V_{CC}=800V$, $V_{GS}=+15V/-4V$, $I_D=60A$
Inductive Load




Figure 16. E_{on} , E_{off} vs R_g

$T_j=150^\circ C$, $V_{CC}=800V$, $V_{GS}=+15V/-4V$, $I_D=60A$
Inductive Load




Figure 17. E_{on} , E_{off} vs I_{DS}

$T_j = 25^\circ\text{C}$, $V_{CC} = 800\text{V}$, $V_{GS} = +15\text{V}/-4\text{V}$

$R_{gon} = R_{goff} = 1.0\Omega$, Inductive Load




Figure 18. E_{on} , E_{off} vs I_{DS}

$T_j = 150^\circ\text{C}$, $V_{CC} = 800\text{V}$, $V_{GS} = +15\text{V}/-4\text{V}$

$R_{gon} = R_{goff} = 1.0\Omega$, Inductive Load




Figure 19. C_{ies} , C_{oss} , C_{rss} vs V_{DS}

$T_j = 25^\circ\text{C}$, $f = 1\text{MHz}$, $V_{AC} = 25\text{mV}$

IMPORTANT NOTICE:

This product data sheet describes the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively under the terms and conditions of the supply agreement. There will be no guarantee or of any kind for the product and its characteristics.

The data contained in this document is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the product's suitability for the intended application and the completeness of the product data concerning such application.

Due to technical requirements, our product may contain dangerous substances. For information on the types in question, please contact the sales staff responsible for you.

Changes to this product data sheet are reserved.

Please contact the sales staff (Sales@leapers-power.com) for further information on the product, technology, delivery terms, conditions and prices.