

Description

The DFS360HF12DFC1 is a Half Bridge SiC MOSFET Power Module. It integrates high performance SiC MOSFET chips designed for the applications such as Motor drives and Renewable energy.



Features

- Blocking voltage:1200V
- $R_{ds(on)} = 4.3m\Omega$
- Low thermal resistance with Si₃N₄ AMB
- 175°C maximum junction temperature
- 62mm halfbridge module

Applications

- Motor Drives
- Vehicle Fast Chargers
- Renewable energy
- UPS

Circuit diagram




Figure 1. Out drawing & circuit diagram for DFS360HF12DFC2

Pin Configuration and Marking Information




Figure 2. Pin configuration

Module

Parameter	Conditions	Value	Unit
Isolation Voltage	RMS, f=50Hz, t =1min	3.4	kV
Material of module baseplate	-	Cu	-
Creepage distance	terminal to heatsink terminal to terminal	14.5 10	mm
Clearance	terminal to heatsink terminal to terminal	12.5 10	mm
CTI	-	200	-
Module lead resistance, terminals – chip	T _c =25°C	0.6	mΩ
Mounting torque for module mounting	M6	4 to 6	Nm
Weight	-	320	g

Maximum Ratings (T_j =25°C unless otherwise specified)

Symbol	Parameter	Conditions	Ratings	Unit
V _{DSS}	Drain-Source Voltage	G-S Short	1200	V
V _{GSS}	Gate-Source Voltage	D-S Short, AC frequency ≥ 1Hz, Note1	-10 to 22	V
I _{DS}	DC Continuous Drain Current	T _c =25°C , V _{GS} =18V	480	A
I _{DS}	DC Continuous Drain Current	T _c =80°C , V _{GS} =18V	360	A
I _{SD}	Source-Drain Current(diode)	T _c =25°C, with ON signal	480	A
I _{SD}	Source-Drain Current(diode)	T _c =80°C, with ON signal	360	A
I _{DSM}	Pulse Drain Current	T _c =25°C, Pulse width =1ms, V _{GS} =18V, Note2	800	A
P _{tot}	Total Power Dissipation	T _c =25°C	1500	W
T _{jmax}	Max Junction Temperature	-	175	°C
T _{stg}	Storage Temperature	-	-40 to 125	°C

Note1: Recommended Operating Value, +18V/-5V, +18V/-4V, +15V/-4V

Note2: Pulse width limited by maximum junction temperature

Preliminary datasheet_Ver.A EN

www.leapers-power.com

MOSFET Electrical characteristics (T_j=25°C unless otherwise specified, chip)

Symbol	Item	Condition		Value			Unit
				Min.	Typ.	Max.	
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =400uA		1200	-	-	V
I _{DSS}	Zero gate voltage drain Current	V _{DS} =1200V, V _{GS} =0V		-	4	-	μA
V _{GS(th)}	Gate-source threshold Voltage	I _D =140mA, V _{DS} =V _{GS}	T _j =25°C	1.8	2.7	-	V
			T _j =175°C	-	2.05	-	V
I _{GSS}	Gate-Source Leakage Current	V _{GS} =20V, V _{DS} =0V	T _j =25°C	-	-	400	nA
R _{DS(on)} (Chip)	Static drain-source On-state resistance	I _D =360A V _{GS} =+15V	T _j =25°C	-	5.3	-	mΩ
			T _j =175°C	-	7.5	-	mΩ
		I _D =360A V _{GS} =+18V	T _j =25°C	-	4.3	-	mΩ
			T _j =175°C	-	6.4	-	mΩ
V _{DS(on)} (Chip)	Static drain-source On-state Voltage	I _D =360A V _{GS} =+15V	T _j =25°C	-	1.91	-	V
			T _j =175°C	-	2.70	-	V
		I _D =360A V _{GS} =+18V	T _j =25°C	-	1.55	-	V
			T _j =175°C	-	2.30	-	V
C _{iss}	Input Capacitance	V _D =800V, V _{GS} =0V f =100kHz, V _{AC} =25mV		-	23260	-	pF
C _{oss}	Output Capacitance			-	708	-	pF
C _{rss}	Reverse transfer Capacitance			-	57	-	pF
R _{Gint}	Internal gate resistor	f =100kHz, V _{AC} =25mV		-	1.6	-	Ω
Q _g	Total gate charge	V _{DD} =800V, I _D =240A, V _{GS} =+18/-4V		-	840	-	nC
t _{d(on)}	Turn-on delay time	V _{DD} =600V I _D =360A V _{GS} =+18/-4V R _{gon} /R _{goff} =5.0Ω/5.0Ω	T _j =25°C	-	97	-	ns
			T _j =150°C	-	78	-	
t _r	Rise time		T _j =25°C	-	59	-	ns
			T _j =150°C	-	48	-	
t _{d(off)}	Turn-off delay time		T _j =25°C	-	192	-	ns
			T _j =150°C	-	204	-	
t _f	Fall time			T _j =25°C	-	58	-

		Inductive load switching operation	T _j =150°C	-	62	-	
E _{on}	Turn-on power dissipation		T _j =25°C	-	11.1	-	mJ
			T _j =150°C	-	10.6	-	
E _{off}	Turn-off power dissipation		T _j =25°C	-	12.3	-	mJ
			T _j =150°C	-	13.4	-	
R _{th(j-c)}	FET Thermal Resistance	Junction to Case		-	0.10	-	°C /W

Body Diode Electrical characteristics (T_j=25°C unless otherwise specified, chip)

Symbol	Item	Condition		Value			Unit
				Min.	Typ.	Max.	
V _{SD}	Body Diode Forward Voltage	V _{GS} =-5V I _{SD} =360A	T _j =25°C	-	6.0	-	V
			T _j =175°C	-	5.3	-	
T _{rr}	Reverse recovery time	V _{DD} =600V I _D =360A	T _j =25°C	-	51	-	ns
			T _j =150°C	-	98	-	
Q _{rr}	Reverse recovery charge	V _{GS} =+18/-4V R _{gon} /R _{goff} =5.0Ω/5.0Ω	T _j =25°C	-	2.3	-	uC
		Inductive load	T _j =150°C	-	9.0	-	
		switching operation	T _j =25°C	-	0.36	-	mJ
E _{rr}	Diode switching power dissipation		T _j =150°C	-	1.24	-	

Test Conditions




Figure 3. Switching time measure circuit




Figure 4. Switching time definition




Figure 5. I_{DS} vs V_{DS}

$T_j = 25^\circ\text{C}$




Figure 6. I_{DS} vs V_{DS}

$V_{GS} = +18\text{V}$




Figure 7. $I_{SD}(I_F)$ vs $V_{SD}(V_F)$

$T_j = 25^\circ\text{C}$, V_{GS} parameter




Figure 8. $I_{SD}(I_F)$ vs $V_{SD}(V_F)$

$T_j = 175^\circ\text{C}$, V_{GS} parameter




Figure 9. $R_{DS(ON)}$ vs T_j

$V_{GS} = +15V/+18V$, $I_D = 360A$, $1.0X = 4.3m\Omega$




Figure 10. $R_{DS(ON)}$ vs I_{DS}

$V_{GS} = +18V$, $1.0X = 4.3m\Omega$




Figure 11. V_{GS} vs Q_g

$V_{DS} = 800V$, $I_D = 240A$, $T_j = 25^\circ C$




Figure 12. $V_{GS(TH)}$ vs T_j

$V_{GS} = V_{DS}$, $I_D = 140mA$




Figure 13. E_{on} , E_{off} , E_{rr} vs R_g

$T_j=25^{\circ}\text{C}$, $V_{DD}=600\text{V}$, $V_{GS}=+18\text{V}/-4\text{V}$, $I_D=360\text{A}$

Inductive Load




Figure 14. E_{on} , E_{off} , E_{rr} vs R_g

$T_j=150^{\circ}\text{C}$, $V_{DD}=600\text{V}$, $V_{GS}=+18\text{V}/-4\text{V}$, $I_D=360\text{A}$

Inductive Load




Figure 15. E_{on} , E_{off} , E_{rr} vs I_{DS}

$T_j=25^{\circ}\text{C}$, $V_{DD}=600\text{V}$, $V_{GS}=+18\text{V}/-4\text{V}$

$R_{gon}/R_{goff}=5.0\Omega/5.0\Omega$, Inductive Load




Figure 16. E_{on} , E_{off} , E_{rr} vs I_{DS}

$T_j=150^{\circ}\text{C}$, $V_{DD}=600\text{V}$, $V_{GS}=+18\text{V}/-4\text{V}$

$R_{gon}/R_{goff}=5.0\Omega/5.0\Omega$, Inductive Load

IMPORTANT NOTICE:

This product data sheet describes the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively under the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

The data contained in this document is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the product's suitability for the intended application and the completeness of the product data concerning such application.

Due to technical requirements, our product may contain dangerous substances. For information on the types in question, please contact the sales staff responsible for you.

Changes to this product data sheet are reserved.

Please contact the sales staff (Sales@leapers-power.com) for further information on the product, technology, delivery terms, conditions and prices.